

YEM[®]

HD PORTABLE DOWN CONVERTER

HDC-2000

FEATURES

- Converts HD analog signals (Y/Pb/Pr) to SD serial digital signals (4:2:2) and analog composite signals.
- Responds to 3 input signal formats such as 1080/23.976PsF, 1080/29.97PsF, and 1080/59.94i. Available 1080/50.00i as an option.
- Output signal format: 525/59.94i (NTSC). Available 625/50.00i (PAL) output with as an optional 1080/50.00i input.
- 2:3 pull-down processing at PsF input.
- Available 3 Aspect Ratio Conversion (squeeze/letter box/edge crop).



YEM, the leading company of the HD technology, offers the "HDC-2000", a down converter, which is highly regarded in various fields for not only its high-quality images but also the technological prowess and reliability.

HDC-2000**INPUT**

HD Analog	Y/Pb/Pr 1.0/0.7/0.7Vp-p 75Ω, BNC
INPUT FORMAT	① 1080/23.976PsF
	② 1080/29.97PsF
	③ 1080/59.94i
	④ 1080/50.00i (option)

OUTPUT

SD SDI	4:2:2 Conforming to SMPTE259M, BNC 1 OUTPUT
COMPOSITE VIDEO	1.0Vp-p 75Ω, BNC 1 OUTPUT
OUTPUT FORMATS	525/59.94i for input signals①, ② and ③
	625/50.00i for input signals④ (option)

VOLTAGE

DC 12V battery pack (Sony XLR 4P)

MEASUREMENTS & WEIGHT

184(W)×326(D)×44(H)mm, Approx. 2.5kg

