## **BLCD-500SNPA**

## 5 인치 Rack Type LCD Monitor





제품사진

사용예)

Feature: The 500SNPA has four independently controlled 5" active matrix LCD panels. Which fits in live broadcasting especially. These 5" panels have 960 x 234 pixels producing a true high resolution image. This unit also has a unique feature that allows the unit to tilt up or down for optimum viewing angle. There are three buttons to adjust tint brightness and volume on the front of panel. The unit includes power supply, instructions and specification for your reference.

## *Feature*

I High Resolution, LCD panel, 960\*234 pixels, 224, 640 total.

I Wide viewing angle of view - 120° horizontal provides superior visibility when the viewer is not directly in front of the screen.

I 350 candelas per square meter (cd/m2) luminance produces excellent image quality in varying light and viewing

I Automatic NTSC/PAL Video Signal Detection, screen will turn blue with the absence of input signal

I 150:1 contrast ratio with response rates less than 30 ms results in excellent quality for moving images

14:3 screen aspect ratios for DTV operations


I Convenient front panel controls with dedicated input and ratio selections and adjustments

500SNPA

## Specification

Part number

Single screen model	SOONPA
Adust angle	Up/down 600
Input Voltage	DC12V
Power	≤24₩/2A
Weight	4kg
Dimension	785mm×215mm×85mm (L×H×D)
Products Name: Single monitor model: Screen size: Aspect Ratio: Resolution: Dot pitch: Brightness: Contrast: Response Time: Video angle Color system: Audio input: Video input: Input voltage: Votage: Wording temperature: Power: Size: Total weight:	5* 4:3 960×234 0.136×0.416(mm) 350cd/m² 150:1 30ms(entity/ms) Left/right/up/down 60°/60° /15°/35° PAL/NTSC(automatic recognition) 1line voice input(single channel) 1line composite video input DC12V DC12V-24V(internal short-circuit protection function)



TEL: 02-579-9126~8 FAX: 02-579-9129 E-MAIL: sales@baek-doo.com