

BLCD-640SNPA

6.4 인치 Rack Type LCD Monitor



제품사진



사용 예)

The 640SNPA has four independently controlled 6.4" active matrix LCD panels. Which fits in live broadcasting especially. These 6.4" panels have 960 x 234 pixels producing a true high-resolution image. This unit also has a unique feature that allows the unit to tilt up or down for optimum viewing angle. There are three buttons to adjust tint brightness and volume on the front of panel. The unit includes power supply, instructions and specification for your reference.

Feature

- I High Resolution, LCD panel, 960*234 pixels, 224, 640 total.
- I Wide viewing angle of view - 120° horizontal provides superior visibility when the viewer is not directly in front of the screen.
- I 350 candelas per square meter (cd/m²) luminance produces excellent image quality in varying light and viewing condition.
- I Automatic NTSC/PAL Video Signal Detection, screen will turn blue with the absence of input signal
- I 150:1 contrast ratio with response rates less than 30 ms results in excellent quality for moving images
- I 4:3 screen aspect ratios for DTV operations
- I Convenient front panel controls with dedicated input and ratio selections and adjustments

Specification

Part number	640SNPA
Single screen model	640NPA
Adjust angle	Up/down 60°
Input Voltage	DC12V
Power	≤36W/2A
Weight	4.7kg
Dimension	885mm×230mm×85mm(L×H×D)

Specification parameter

Products Name:	Portable Modular Color LCD Monitor
Single monitor model:	640NPA
Screen size:	6.4"
Aspect Ratio:	4 : 3
Resolution:	960×234
Dot pitch:	0.136×0.416(mm)
Brightness:	350cd/m ²
Contrast:	150:1
Response Time:	30ms(entity/ms)
Video angle	Left/right/up/down 60°/60° /15°/35°
Color system:	PAL/NTSC(automatic recognition)
Audio input:	1line voice input(single channel)
Video input:	1line composite video input
Input voltage:	DC12V
Voltage:	DC12V-24V(internal short-circuit protection function)
Working temperature:	-20℃~60℃
Power:	≤9W/0.75A
Size:	183mm×149mm×40mm
Total weight:	About 0.57kg



BAEKDOO
INTERSYSTEMS
CO.,LTD.
백두인터시스템(주)

TEL: 02-579-9126~8
FAX: 02-579-9129
E-MAIL: sales@baek-doo.com
Homepage: www.baek-doo.com