BLCD-640YNPA

6.4 인치 Rack Type LCD Monitor





제품사진

사용예)

640YMPA has two independently controlled 6.4" active matrix LCD panels Which fits in The live broadcasting especially. These 6.4" panels have 960 x 234 pixels producing a true high resolution image. The flexible input configuration with standard inputs and active loop through for composite video plus a multi-format connector for HD or SD analog component signals (SMPTE274M). This unit also has a unique feature that allows the unit to tilt up or down for optimum viewing angle.. There are three buttons to adjust tint brightness and volume on the front of panel. The unit includes power supply, instructions and specification for your reference.

Feature

I High Resolution, LCD panel, 960 x 234 pixels, 224,640 total.

I Wide viewing angle of view - 120° horizontal provides superior visibility when the viewer is not directly in front of the

I 350 candelas per square meter (cd/m2) luminance produces excellent image quality in varying light and viewing condition.

I Automatic NTSC/PAL Video Signal Detection, screen will turn blue with the absence of input signal

I 150:1 contrast ratio with response rates less than 30 ms results in excellent quality for moving images

I Standard Multiformat inputs: Component Analog HD/SD, Composite Video PAL/NTSC.

14:3 screen aspect ratios for DTV operations

Specification

Products Name: Single monitor model: Portable Modular Color LCD Monitor 640YNPA

Screen size: Aspect Ratio

4 - 3

960×234 Resolution:

Dot pitch: 0.136×0.416(mm)

Brightness: 350cd/m² Contrast 150:1

Response Time: 30ms(entity/ms)

Video angle Left/right/up/down 600/600 /150/350 Color system: PAL/NTSC(automatic recognition) Audio input: 1line voice input(single channel)

1line composite video input

Input voltage: Votage: DC12V DC12V-24V(internal short-circuit protection function)

Wording temperature: -20°C~60°C

≤18W/1.5A Power:

183mm×149mm×40mm About 0.57kg Total weight:

Part number	640YNPA	
Single screen model	640NPA	
Adust angle	Up/down 45 ⁰	
Input Voltage	DC12V~24V	
Power	18W/1.5A	
Weight	4.2kg	
Dimension	256mm×345mm×256mm(L×H×D)	

