



BAEKDOO
INTERSYSTEM
CO., LTD

QuadView® 2 + 2



Input 1

Input 2

Input 3

Input 4

Output

Quadview 2+2

4

2

RGB/DVI /HD

4

Composite/S-Video

4

가

가

가

Quad split, Side by side, Picture in picture

Overlapping windows

KEY FEATURES:

- RGB, DVI, HDTV, S-Video, NTSC / PAL inputs
- Inputs to 1920 X 1200 pixels
- Output to 1920 X 1200 pixels
- Smoothly size and position inputs
- Zoom areas of interest
- Ethernet and RS-232 control
- Web operation
- 24 presets
- 4:3 and 16:9 displays
- Colored backgrounds
- Titles and borders
- RGB/DVI output

KEY APPLICATIONS:

board Rooms
Training Facilities
Video Conferencing
Staging
Meeting Rooms
Electronic Signage
Education
Home Theater



BAEKDOO
INTERSYSTEM
CO., LTD

Tel : (02) 579-9126~8, 575-6432

Fax: (02) 579-9129

Input Signals

type / Number	2x RGB / Y P _b P _r / HDTV / DVI on DVI-I connectors 4x Composite Video 4x S-Video
Resolution	640 x 480 to 1920 x 1200 pixels 720p, 1080i, and 1080p HDTV
Horizontal scan rate	12 kHz to 125 kHz interlaced or non-interlaced
Frame rate	Up to 200Hz
Video levels	0.7 V p-p
Sync type	Sync on green, separate composite sync, or separate H-drive and V-drive


Output Signals

Type	RGB, DVI on DVI-I connector
Resolution	640 x 480 to 1920 x 1200 pixels
Horizontal scan rate	12 kHz to 125 kHz interlaced or non-interlaced
Video levels	0.7 V p-p
Sync type	Sync on green, separate composite sync, or separate H-drive and V-drive

Other

Power	90 - 264 VAC 47Hz - 63 Hz Less than 40 W
Control	Ethernet 10 / 100 Base-T Rs - 232 Web interface
Size	1 RU Width 17.25" (43.8cm) Depth 11.7" (29.7cm) Height 1.75" (4.5cm) Rackmount kit included
Weight	Approximately 12 lbs. (5.45 kg)

Front Panel



Rear Panel

